



Powered by
150lm/w, LM-80 Listed

• Water Resistant
• Dust Proof

Rubycon Capacitor



Available:
Mogul Base (E39/EX39/E40)



Hollow heat sink, ventilation design increase air reflow.



Driver separate/ Air Gap design, insulate thermal transmission between driver and LED.

Applications



Acorn



Globe



Lantern



Tear Drop



High Bay

Product Advantages:

- Ventilation heat sink design, gap separated with driver base, insulate thermal transmission and increase more cooling surface areas.
- For totally enclosed fixture using.
- IP65 waterproof design, use for wet location.
- Compatible with certain confirmed ballasts.
- 6000V high voltage surge protection.
- High lumen effect: 150lm/W.
- UL/CUL/DLC4.0/FCC/CE/RoHS Certificated.
- 5 years warranty.
- IES files, ISTMT, LM79, LM80 test reports are available.
- Retrofit replacement for conventional HID/MH/HPS lamps, Post top, Teardrop, Canopy light, High bay fixture, etc.



80W



100W



120W

Item NO.	Watt	Lumen	Dimension	CCT	Voltage	CRI	PF	Beam Angle	IP Rating
ML-360D-K4- II -80W	80W	12000lm	Φ140*230mm	3000K	AC100-300V	>80	>0.9	360°	IP65
ML-360D-K4- II -100W	100W	15000lm	Φ140*245mm	4000K					
ML-360D-K4- II -120W	120W	18000lm	Φ140*265mm	5000K					
				6000K					

LED Brand SAMSUNG 2835 / EPISTAR 2835
 Housing 6063 Aluminum+Retardant PC
 Capacitors RUBYCON
 Glue DOW CORNING

Base Type
 Test Standard
 Safety Certification
 Warranty Time

E39/EX39/E40
 IES/IP65/LM79/LM80
 DLC/UL/FCC/CE/RoHS
 5 Years

Product Advantages:

- Ventilation heat sink design, gap separated with driver base, insulate thermal transmission and increase more cooling surface areas.
- For totally enclosed fixture using.
- IP65 waterproof design, use for wet location.
- Compatible with certain confirmed ballasts.
- 6000V high voltage surge protection.
- High lumen effect: 150lm/W.
- UL/CUL/DLC4.0/FCC/CE/RoHS Certificated.
- 5 years warranty.
- IES files, ISTMT, LM79, LM80 test reports are available.
- Retrofit replacement for conventional HID/MH/HPS lamps, Post top, Teardrop, Wall pack, Low bay fixture, etc.



V4.0



27W



36W



45W



54W



75W

Item NO.	Watt	Lumen	Dimension	CCT	Voltage	CRI	PF	Beam Angle	IP Rating
ML-360D-K10-27W	27W	4050lm	Φ95*185mm						
ML-360D-K10-36W	36W	5400lm	Φ95*210mm	3000K					
ML-360D-K10-45W	45W	6750lm	Φ95*235mm	4000K	AC100-300V	>80	>0.9	360°	IP65
ML-360D-K10-54W	54W	8100lm	Φ95*260mm	5000K					
ML-360D-K10-75W	75W	11250lm	Φ95*305mm	6000K					

Light Effect 150lm/w±10%
 Surge Voltage 6000V
 Lifespan 50000hrs

Base Type E26/E27/E39/EX39/E40
 Test Standard IES/IP65/LM79/LM80
 Safety Certification DLC/UL/FCC/ CE/RoHS
 Warranty Time 5 Years

Product Advantages:

- Ventilation heat sink design, gap separated with driver base, insulate thermal transmission and increase more cooling surface areas.
- For totally enclosed fixture using.
- IP65 waterproof design, use for wet location.
- Compatible with certain confirmed ballasts.
- 6000V high voltage surge protection.
- High lumen effect: 150lm/W.
- UL/CUL/DLC4.0/FCC/CE/RoHS Certificated.
- 5 years warranty.
- IES files, ISTMT, LM79, LM80 test reports are available.
- Retrofit replacement for conventional HID/MH/HPS lamps, Downlight, Mini wallpack, Bollard light, Garden global light, etc.



V4.0



16W



22W



28W

Item NO.	Watt	Lumen	Dimension	CCT	Voltage	CRI	PF	Beam Angle	IP Rating
RMS-360D-K11-16W	16W	2400lm	Φ 75*165mm	3000K	AC100-300V	>80	>0.9	360°	IP65
RMS-360D-K11-22W	22W	3300lm	Φ 75*180mm	4000K					
RMS-360D-K11-28W	28W	4200lm	Φ 75*220mm	5000K 6000K					

Light Effect 150lm/w±10%
 Surge Voltage 6000V
 Lifespan 50000hrs

Base Type E26/E27/E39/EX39/E40
 Test Standard IES/IP65/LM79/LM80
 Safety Certification DLC/UL/FCC/ CE/RoHS
 Warranty Time 5 Years